

S-SERIES LED STREET LIGHT

- High intensity die-cast aluminum body
- 0-120° angle adjustable and applicable different mounting arm
- Replaceable and upgradeable modular design, easy assembly, easy installation and easy maintenance
- High luminous flux 130-150lm/W
- Photocell, surge protector, wireless single lamp controller optional
- The complete optical designs, can reach the lighting demand of the various optical applications



Specifications

Model No.	INNO-SSL60W	INNO-SSL100W	INNO-SSL150W	INNO-SSL200W	INNO-SSL240W
Power	60W	100W	150W	200W	250W
Lumens	7,500LM	12,500LM	18,750LM	25,000LM	30,000LM
Efficacy	125LM/W	125LM/W	125LM/W	125LM/W	125LM/W
CRI	>70	>70	>70	>70	>70
Voltage	AC100-277V	AC100-277V	AC100-277V	AC100-277V	AC100-277V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
PF	> 0.9	> 0.9	> 0.9	> 0.9	> 0.9
CCT	5700K	5700K	5700K	5700K	5700K
Beam Angle	0-180°	0-180°	0-180°	0-180°	0-180°
Working Temp.	-40°C to 60°C	-40°C to 60°C	-40°C to 60°C	-40°C to 60°C	-40°C to 60°C
IP Rating	IP67	IP67	IP67	IP67	IP67
Warranty	5 years	5 years	5 years	5 years	5 years
Size (inch)	19.6 x 12.6 x 3.3 inch	22.6 x 12.6 x 3.3 inch	25.6 x 12.6 x 3.3 inch	28.5 x 12.6 x 3.3 inch	31.5 x 12.6 x 3.3 inch